



BLACK MAX 3

PRODUCT DESCRIPTION

BLACK MAX is a unique proprietary formula designed to provide a bituminous protective coating, available as an easy-to-use heavy-duty brushable coating with or without fibres.

USED FOR

Designed for use as a protective coating for structures, posts, and voids to provide a durable bituminous flexible membrane.

ADVANTAGES OF USE

- Rapid film formation time.
- Water resistant film formed.
- Water-based, Utilises low VOC formula.
- Meets Green Star Rating.
- Economical.
- Easy to use and clean-up.

DIRECTIONS

Mix thoroughly before use.

Apply BLACK MAX by brush, roller, or high-pressure airless spray, at a rate of 1m²/L.

Avoid excessive buildup or film thickness of product, this may affect the products ability to properly cure.

Apply 2-3 coats, allowing the product to dry for a min 4 hours. Additional coats should be applied north-south, east-west to ensure even coverage.

Do not apply BLACK MAX when the temperature is below 5deg C or above 40 deg C or if rain is imminent.

LIMITATIONS

BLACK MAX may be compatible with certain paints, adhesives for vinyl tiles, or other types of resilient flooring may be applied to concrete coated with Black Max.

BLACK MAX should be allowed to thoroughly cure prior to such application, and that a test area has been completed for approval.

The life of BLACK MAX will depend on the weather exposure conditions to which it has been subjected.

The bond of BLACK MAX is likely to fail if the product is applied to concrete or masonry substrates subject to back water pressure.

A black appearance is obtained.

APPLICATION

COVERAGE RATE	THICKNESS
1m ² /L - 1mm WFT	0.65mm DFT

TECHNICAL DATA

COVERAGE	1m ² per litre - 1mm WFT
CLEAN UP	Water when wet.
FIRST AID, SAFETY & STORAGE	Refer to Material Safety Data sheet.
PACKS	4L, 15L, 20L, 200L



COLORO BLACK MAX - TDS MAY 2026

This Product Data Sheet (PDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this PDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the way, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Chemical House does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether in accordance with any advice, specification, recommendation, or information given by it.

CHEMICAL HOUSE

9 Production Avenue, Molendinar
Queensland, 4214 Australia
Ph: +61 7 5594 0344